



Wall Mount HVAC Unit P-5215



Reduce Downtime and Increase Operator Safety.

The Polar P-5215 Wall Mount HVAC is built to withstand the harshest environments around the world! Perfect for a wide variety of industries, this unit is designed to perform consistently in the roughest surroundings and extremely high-temperature conditions.

With proven longevity using high-quality parts, the P-5215 will save you money on spare parts, lost time between failures and replacement part serviceability!

Make Your Equipment ISO 23875 Compliant

The P-5215 is designed to allow for the seamless integration of Sy-Klone technology for ISO 23875 Certification! **No need for additional installation fees!** Simply order the Sy-Klone CF2 Pressurizer, CFX2 Recirc-filtration unit, Pressure and CO₂ monitor with your air-conditioner.

Comes pre-installed and controlled right through the HVAC!



FEATURES & BENEFITS

- Dimensions: 35" wide x 64" tall x 16.5" deep; weight: ~450 Lbs
- 30,000 - 36,000 Btu Cooling @ 75°F WB
- 4 kW to 6 kW Electric Heating
- Stainless Steel Housing
- Antimicrobial Copper/Copper Coils
- 40,000 hour sealed brushless evaporator blower IP68/IP6K9K
- 40,000 hour sealed brushless condenser fan with automatic reverse mode to clean coil in high dust environments IP68/IP6K9K
- Polar digital controller
- Seamless integration of Sy-Klone technology for ISO 23875 certification

AVAILABLE OPTIONS

- Forward only condenser fan
- Air-conditioning only
- Sy-Klone Cab Pressurizer, Recirc and Monitor

Wall Mount HVAC Unit

P-5215



PART NUMBER

INPUT VOLTAGE

FLA

P-5215-H-230P*

208-240 VAC 1 Ph 50/60 Hz

45 A

P-5215-H-230-3P

208-240 VAC 3 Ph 50/60 Hz

30 A

P-5215-H-480-3P

460-480 VAC 3 Ph 50/60 Hz

20 A

*Special Order



PROUDLY SERVING THE WORLD SINCE 1981

1-800-309-8155 • INFO@POLARMOBILITY.COM
POLARMOBILITY.COM

Design and specifications are subject to change without notice.